

Wood Grain Glaze

CIFS® Wood Grain Glaze used artistically over Wood Grain Tex specialty finish creating the look of wood with the durability of an acrylic finish and is formulated with DuroTone pigments for excellent color retention.

Coverage per pail

1000-1200 sf/pail (93-112 sm)

Coverage may vary depending upon application technique and surface conditions.

Packaging/Shelf Life/Storage

Packaging: 5 gallon (19L) pail

Pail Weight: 53 lbs (24 kg)

Shelf Life: 2 years

Storage: Protect from extreme heat (90°F (32°C)), freezing and direct sunlight.

Hazard: This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

VOC: Less than 50 g/L.

Health & Safety

Precautionary Statement

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID MEASURES

Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact: Wash skin with soap and water.

Inhalation: Move to fresh air.

Ingestion: Clean mouth with water and afterwards drink plenty of water.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) in the Products section at masterwall.com for further health and safety information.

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.

Features & Benefits

- 100% Acrylic Polymers for durability
- Vapor Permeable - resists blistering and allows trapped water vapors to pass
- Water Based - easy clean up with water
- Tinted to CIFS® Wood Grain colors

Application Temperature: 40°-110°F (5°-43°C) • Dry to Touch: 1/2 hr • Dry Time: 12 hrs

at room temperature, working and drying time will vary with temperature and humidity

Application Procedure

Job Conditions - Air and substrate temperature for application of Wood Grain Glaze must be 40°F (5°C) or higher and must remain 40°F (5°C) or higher for a minimum of 24 hours. Provide temporary protection until Wood Grain Glaze is fully dried. Store materials within prescribed temperature limits and out of direct sunlight. Working and drying times are based upon normal room temperature conditions and will vary with temperature and humidity.

Preparation - The Wood Grain Tex Finish must be clean, dry and ready to receive the acrylic coating.

Equipment Needed - Brush, 4"-6" (102-154 mm) Foam Roller, Spray bottle with water, Wood Grain Tool (Available from Master Wall®), Wood Grain Sealer.

Mixing - Thoroughly stir Wood Grain Glaze into a homogenous consistency. Small amounts of clean, potable water may be added to obtain a workable consistency. Do not over mix. Do not exceed 24 ounces (0.7L) of water per pail. Do not add accelerators or retarders to Wood Grain Glaze.

Application - Wood Grain Glaze is applied by brush or a moist foam roller.

Using a paint brush for latex paints, brush Wood Grain Glaze into the grooves of the finish.

Using a moist foam roller, roll a thin amount of Wood Grain Glaze onto the finish surface and keep a wet edge.

Using a spray bottle, wet the surface of the Wood Grain Glaze to thin and keep from tacking too quickly.

Add grain to the surface using the Wood Grain Tool along the length of the grooved finish, rocking the tool to create the desired pattern.

Once dry to the touch, lightly sand the surface if needed using 100-grit sandpaper to remove any high spots or heavy stain areas.

Using a sponge or foam roller, cover the entire surface with Wood Grain Sealer.

Clean Up

Tools and equipment can be cleaned with soapy water when Wood Grain Glaze is wet.

Limitations

Do not use Wood Grain Glaze as a finish directly over any Master Wall base coat.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2020 Master Wall Inc.®



masterwall.com