



Wood Grain Sealer

Surface Sealer and Protectant for CIFS® Wood Grain

Approved Substrates
Wood Grain Tex & Glaze
Others approved in writing

Manufacture Locations:
30058 • 77474 • 84651
Recycled Content: 0%
VOC 100 g/L

Packaging: 5 gallon (19L) pail
Pail Weight: 43 lbs (19.5 kg)
Coverage (estimated):
800-1000 sf/pail (74-93 sm)
Dry to Touch: 10 minutes @
room temperature
Recoat Time: 6 hours @ room
temperature
Drying Time: 6 hours @ room
temperature
Application Range: 45°-110°F
(7°-43°C)
Shelf Life: 2 years

To **finish strong** you need a crystal clear penetrating sealer and protectant that protects from UV deterioration and is vapor permeable. Wood Grain Sealer adds depth, tone and highlight to CIFS® Wood Grain applications.

Application Procedure

Job Conditions - Air and substrate temperature for application of Wood Grain Sealer must be 45°F (7°C) or higher and must remain 45°F or higher for a minimum of 24 hours.

Temporary Protection – Must be provided at all times until the Wood Grain Sealer has dried.

Surface Preparation - Surface temperature must be above 45°F (7°C). Surface must be clean, dry, structurally sound and free of efflorescence, oil, grease, form release agents, and curing compounds. On previously painted surfaces, all loose, peeling and chalking paint must be removed. Any glossy areas must be sanded.

Wood Grain Tex & Glaze —Surfaces must be clean and dry. Clean existing surfaces following recommended and accepted practices. Tones will deepen and a sample is recommended for approval.

Mixing - Thoroughly stir Wood Grain Sealer into a homogenous consistency. In the pail, Wood Grain Sealer will have a milky white color. Avoid introducing air into the coating. Do not over mix. Do not add accelerators or retarders to Wood Grain Sealer.

Application – Wood Grain Sealer can be applied by brush, roller, or airless spray equipment. When using a roller, a sponge roller is recommended. Apply Wood Grain Sealer in an even, continuous coat, maintaining a wet edge. Wood Grain Sealer will apply milky white and dry clear.

Clean Up

Tools and equipment can be cleaned with water when Wood Grain Sealer is wet.

Limitations

Wood Grain Sealer should not be used as a primer color coat.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information.
© 2019 Master Wall Inc.®



masterwall.com

PO Box 397 • Fortson • GA • 31808 • 800-755-0825