



Accent Stucco Swirl



Accent Stucco Fine Sand
Accent DuroTex Fine



Accent Stucco Medium Sand
Accent DuroTex Medium



Accent Stucco Versatex

- **Stucco Grade Finish available in Standard Acrylic and Elastomeric Plus versions**
- **Dirt Pickup Resistant (DPR) 100% Acrylic Polymers**
- **Integrally Colored with 64 Standard Colors**
- **Durable Aggregate**
- **Mold/Mildew Resistant**
- **Easily applied to all stucco surfaces**



Stucco Finish

DESCRIPTION

ACCENT® Stucco Finish is a quality textured finish for use over traditional stucco base, One Coat Stucco (OCS), masonry or concrete surfaces. ACCENT® Stucco Finish is available in four different textures and 64 standard colors.

PACKAGING & USE DATA

1. ACCENT® Stucco Finish is packaged in 5 gallon (19 L) pails.
2. Working Time: 1/4 hour @ room temperature.
3. Drying Time: 8-12 hours to set, 48-72 hours to dry @ room temperature. High pigment levels, low temperatures, high humidity extend dry times.
4. Application Range: 40°F (4°C) and 110°F (39°C).
5. Shelf Life: 1 year.

STORAGE

1. Store pails in a cool, dry location between 40°F (4°C) and 110°F (39°C).
2. Store away from direct contact with the ground and/or concrete and out of direct sunlight.
3. Protect pails from weather and other damage.

COVERAGE

Accent Stucco Swirl: 110-140 sf/pail (10-13 sm)

Accent Stucco Fine Sand and DuroTex Fine: 160-170 sf/pail (15-15.8 sm)

Accent Stucco Medium Sand and DuroTex Medium: 120-140 sf/pail (11-13 sm)

Accent Stucco Versatex: Up to 300 sf/pail (27.8 sm) smooth but varies with texture

Coverage will vary by application, applicator skill and substrate conditions. Master Wall Inc.® assumes no responsibility or liability for coverage.

APPLICATION PROCEDURE

Job Conditions - Air and substrate temperature for application of ACCENT® Stucco Finishes must remain within Application Range for a minimum of 24 hours. Provide temporary protection to protect the wall system from damage until permanent flashings, caps and sealants are installed.

Preparation - The substrate must be approved by Master Wall Inc.®, clean, dry, structurally sound and free of efflorescence, oil, grease, form release agents and curing compounds or anything that would affect bond. Painted surfaces are not acceptable and must be removed. Concrete and surfaces should cure for a minimum of 28 days. Stucco should be cured until clean, dry and hard with a pH of 10 or less (typically 14 days), 13 or less if ACCENT® Primer is used.

Mixing - Thoroughly stir ACCENT® Stucco Finish using a heavy duty 1/2" drill at 400 - 500 rpm and a heavy duty mixing paddle. Small amounts of clean, potable water may be added to obtain a workable consistency. To avoid color variations, add the same amount of water to each pail. Do not exceed 24 ounces (0.7L) of water per pail of finish.

Application — Apply a uniform thickness (about 1/16", 1.6 mm) of ACCENT® Stucco Finish to the substrate using a stainless steel trowel. Spread evenly and then scrape the finish coat down to a thickness no greater than the largest aggregate in the material. Immediately float the finish coat using a plastic float to the desired texture. Always maintain a wet edge to achieve uniformity of texture and color.

For Professional Results

1. Apply finish coats away from direct sunlight. Cold joints or color variations can occur if the finish dries too quickly.
2. Consider priming stucco surfaces with ACCENT® Primer to even out finish absorption.
3. Surfaces exposed to the weather must be sloped (6:12 minimum).
4. Under certain conditions dark colors may show efflorescence on the surface during the cure process.
5. Finishes are intended for the approved substrates listed above and are not approved for any EIFS installation.

Clean Up—Tools and equipment can be cleaned with soapy water while the ACCENT® Stucco Finish is still wet.

SAFETY

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. Because handling and use is beyond the control of the manufacturer, our responsibility is limited to the replacement of defective material. ©2023 Master Wall Inc.®



PO Box 397 • Fortson • GA • 31808 • 800-755-0825