



PRODUCT DATA

ACCENT MESH

Accent Mesh is a specially woven, glass fiber mesh for reinforcing stucco surfaces and as a reinforcement for foam shapes used with stucco. Accent mesh improves stucco crack resistance when embedded into Accent Base Coats as a leveling and reinforcement component.

APPLICATION PROCEDURE

Job Conditions - Air and substrate temperature for embedment of the Reinforcing Mesh must be 40°F (5°C) or higher and must remain 40°F (5°C) or higher for a minimum of 24 hours. Provide temporary protection at all times until the wall system, including flashings, caps, and sealants, is completed to provide protection from climatic conditions and other potential damage.

Application - Apply the base coat over the entire surface of the stucco in a thickness greater than that of the Accent Mesh being used, approximately 1/16" (1.6 mm). Immediately embed the Accent Mesh into the wet base coat and smooth from the center to the edge to avoid wrinkles. Lap mesh a minimum of 2-1/2" (63.5 mm) on all sides. The reinforcing fabric must be continuous at all corners and lapped or abutted. The overall minimum thickness of the base coat should be a nominal 1/16" (1.6 mm) when dry.

- Apply in a similar manner over foam shapes used in stucco.
- For inside and outside corners when using Accent Base Coats, the mesh may be lapped up to 12" (305 mm) on each side.
- Apply in a similar manner when embedding into wet stucco brown coat as an external reinforcement without leveling base coat.
- Accent Mesh is intended only for this specific stucco application and not approved for other Master Wall® system applications.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®



Mesh Weight & Coverage*

Weight: 4.4 oz/sy (156 g/sm)
Roll Size: 38" x 150' (96.5 cm x 45.7 m)
Coverage per Roll: 475 sf (44.1 sm)

**All weight and coverage is approximate and depend upon substrate, details and individual application*

Packaging/Storage

Packaging: 4 Rolls per Box

Storage: Keep dry, protect from extreme heat - 90°F (32°C), and direct sunlight.

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.