Master Wall Inc.®
Building a Culture of Excellence

PRODUCT DATA

# WOOD GRAIN SEALER

## CIFS® WOOD GRAIN SPECIALTY FINISH

To finish strong, you need a crystal-clear penetrating sealer and protectant that protects from UV deterioration and is vapor permeable. Wood Grain Sealer adds depth, tone and highlight to CIFS® Wood Grain applications.

## FEATURES & BENEFITS

- Ready to Use
- Dries crystal clear
- 100% acrylic formulation

Application Temperature: 45°-110°F (7°-43°C)

Dry to Touch: 10 minutes @ room temperature

Recoat Time: 6 hours @ room temperature

Drying Time: 6 hours @ room temperature

Working and drying time will vary with temperature and humidity.

## JOB CONDITIONS

Air and substrate temperature for application must be 45°F (7°C) or higher and must remain 45°F (7°C) or higher for a minimum of 24 hours. Provide temporary protection to protect the wall system from damage until permanent flashings, caps and sealants are installed. Store mate-rials within prescribed temperature limits and out of direct sun-light. High temperatures will reduce working times, Low temperatures and/or high humidity will extend working, set and dry times.

## PREPARATION

Wood Grain Tex & Glaze —Surfaces must be clean and dry. Clean existing surfaces following recommended and accepted practices. Tones will deepen and a sample is recommended for approval.

Mixing - Thoroughly stir Wood Grain Sealer into a homogenous consistency. In the pail, Wood Grain Sealer will have a milky white color. Avoid introducing air into the coating. Do not over mix. Do not add accelerators or retarders to Wood Grain Sealer.

### Coverage per pail (sf/sm)*

800-1000 sf/pail (74-93 sm)

**All coverage is approximate and depend upon substrate, details and individual application*

### Packaging/Shelf Life/Storage

Packaging: 5 gallon (19L) pail

Shelf Life: 2 years

Storage: Protect from extreme heat - 90°F (32°C), freezing and direct sunlight.

**Hazard:** This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

**VOC:** Less than 10 g/L.
See Superior Finishes for other technical properties

### Approved Substrates

Wood Grain Tex & Glaze
Others approved in writing

# WOOD GRAIN SEALER

PRODUCT DATA

## APPLICATION PROCEDURE

Wood Grain Sealer can be applied by brush, roller, or airless spray equipment. When using a roller, a sponge roller is recommended. Apply Wood Grain Sealer in an even, continuous coat, maintaining a wet edge. Wood Grain Sealer will apply milky white and dry clear.

## CAUTIONS AND LIMITATIONS

- Wood Grain Sealer should not be used as a primer color coat.

## CLEAN UP

Tools and equipment can be cleaned with water when Wood Grain Sealer is wet.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2026 Master Wall Inc.®

### Health & Safety

**WARNING!**
Causes eye and skin irritation.
Precautionary Statement
Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

**FIRST AID MEASURES**

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Store locked up. Dispose of contents/container in accordance with Local, State, Federal and Provincial regulation.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.

Consult the Safety Data Sheet (SDS) in the Products section at masterwall.com for further health and safety information.

LIMITED WARRANTY
This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.

260701

Master Wall Inc.®
Building a Culture of Excellence

1 Master Wall Ct. • Columbus • GA • 31907 • 800-755-0825 • masterwall.com