



**Master Wall Inc.®**  
Building a Culture of Excellence

## PRODUCT DATA

### DIAMOND COTE

Master Wall Inc.® Diamond Cote is a thick gloss sealer for use over Master Wall® finishes, especially smooth version where a sealer will add protection, deepen the color, and add glossy highlights. High traffic areas where washability is imperative or rooms that experience high humidity, such as bathrooms, should be sealed with Diamond Cote.

### FEATURES & BENEFITS

- Trowel Grade
- Seals and protects
- Crystal Clear
- Gloss Finish
- Sponge or trowel application
- Water-based - easy clean up with water
- Clear top coat for Savannah, Taratex, Travertine, Varius and other finishes

Application Temperature: 53° -110°F (13° -43°C)

Open Time: 1/2 hour

Dry Time: 1-2 hours at room temperature, working and drying time will vary with temperature and humidity.

### JOB CONDITIONS

Air and substrate temperature for application of Diamond Cote must be 53°F (13°C) or higher and must remain above 53°F (13°C) or higher until fully set. Provide temporary protection to protect the wall system from damage until permanent flashings, caps and sealants are installed. Store materials within prescribed temperature limits and out of direct sunlight. High temperatures will reduce working times, Low temperatures and/or high humidity and pigment loading will extend working, set and dry times.

### PREPARATION

After the newly-applied finish has dried, wipe the surface with a clean damp rag to eliminate any dust. Allow the surface to dry.

#### Coverage per pail (sf/sm)\*

Each pail covers 800 to 1200 square feet  
(19.7 to 29.5 sm)

*\*All coverage is approximate and depend upon substrate, details and individual application*

#### Packaging/Shelf Life/Storage

Packaging: 5 gallon (19L) pail

Weight: 40 lbs (18.2 kg)

Shelf Life: 2 years

Storage: Protect from extreme heat 90°F (32°C), freezing and direct sunlight.

## APPLICATION PROCEDURE

Diamond Cote is applied using either a sponge, stainless steel Japanese Trowel or a putty knife. It cannot be rolled, brushed, or sprayed on.

For sponge application dip the sponge into the Diamond Cote and apply to the finish, maintaining a wet surface while working the product into a small area.

Hold the trowel at a 60° angle and scrape a very thin layer of the topcoat onto the dry Venetian Plaster finish. Scrape off any excess using a clean trowel and let this coat dry.

This application will slightly darken the color and will dry to a satin sheen.

## CLEAN UP

Tools and equipment can be cleaned with soapy water while the sealer is still wet.

**Hazard:** This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

**VOC:** Less than 50 g/L.

### Approved Surfaces for Application

Savannah Specialty Finish  
Taratex Specialty Finish  
Travertine Specialty Finish  
Varius Specialty Finish  
Others approved in writing

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2021 Master Wall Inc.®