

Savannah

Savannah is an ultra fine acrylic based finish for interior or exterior use. It features dirt pickup resistant (DPR) for durability and can achieve a variety of looks depending upon finishing techniques. Savannah is highly breathable, mildew resistant and can also be top coated to provide additional surface protection. Savannah can be custom tinted to a wide selection of standard and custom colors, and will provide a longer lasting and more uniform look to the surface.

Coverage per pail

Two-Coat Application:
250-300 sf (23-27.8 sm)

Coverage may vary depending upon application technique and surface conditions.

Packaging/Shelf Life/Storage

Packaging: 5 gallon (19L) pail
Pail Weight: 43 lbs (19.5 kg)
Shelf Life: 2 years
Storage: Protect from extreme heat 90°F (32°C), freezing and direct sunlight.

Technical Data

Hazard: This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

VOC: Less than 50 g/L.

Features & Benefits

- 100% Acrylic Polymers for durability
- Ultra thin application (two coats required)
- Cost effective
- Vapor Permeable - resists blistering and allows trapped water vapors to pass
- Fast set up
- Standard and custom colors
- Can be accented with Vintique, Clearshield, Rollerflex or Metallic Cote
- Water Based - easy clean up with water.

Application Temperature: 40°-110°F (5°-43°C) • Working Time:
1/2 hr • Dry Time: 24 hrs
at room temperature, working and drying time will vary with temperature and humidity

Surface Preparation

Interior Drywall: smooth, flat dust-free and ready for paint. Clean the surface in preparation for Savannah. Prime wall with Primecoat Primer and allow to dry.

Exterior: Master Wall® base coat is required as a leveling coat for all surfaces and shall be smooth and free of any mesh pattern. Scrape or sand base coat so the surface is smooth, level and free of imperfections. Remove any dust caused by the sanding.

Savannah

Health & Safety

WARNING!

Causes eye and skin irritation.

Precautionary Statement

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

Skin Contact: Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Store locked up. Dispose of contents/container in accordance with Local, State, Federal and Provincial regulation.

Spills: Collect with suitable absorbent material such as cotton rags.

Disposal: Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY. Consult the Safety Data Sheet (SDS) in the Products section at masterwall.com for further health and safety information.

LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.

Approved Substrates

Interior Drywall

Master Wall Base Coats

Others approved in writing

Application Procedure

Job Conditions – Air and surface temperatures must be 4°C (40°F) or higher and must remain so for a minimum of 24 hours. Avoid exposure to direct sunlight during application. Protect the finish from rain and temperatures less than 40°F (5° C) for a minimum of 24 hours.

Mixing – Open pail of Savannah and mix approximately one minute with a fixed wheel type paddle or equivalent mixing blade attached to a 1/2" (13 mm) heavy duty drill at 400-500 rpm. Do not add water.

Application – Using a Wind-Lock T-VPF2008, T-VPF2411 or T-VPF2812 Stainless Steel Venetian Plaster Trowel apply a very tight, thin coat of Savannah to the surface free of trowel marks a maximum of 1/16" (1.6 mm) thick. After the first coat has flash dried (5-10 minutes), double back and apply another tight coat. Allow to dry for a minimum of 8 hours and apply another tight, thin coat of Savannah and trowel smooth.

Note: Application problems occur when Savannah is applied too thick. Only paper thin applications are necessary.

Surface may be spray coated after 24 hours with Master Wall® Metallic Cote, Vintique Clearshield or Roller-flex if desired. Follow individual data sheet instructions for products selected.

Cautions and Limitations

- Smaller surface areas achieve a more consistent appearance. Areas larger than 5' x 5' (1.5 x 1.5m) in size can have characteristic mottling.
- Savannah is not intended for deep depressions or irregular surfaces.
- Slope all exterior surfaces 1:2 minimum to shed water.
- Apply in paper thin applications, shrinkage, cracking or blistering can occur over 1/16" (1.6 mm) thick.
- Savannah is designed to be applied over a properly installed interior drywall.
- Not for use over any finishes or primers other than Primecoat.
- Application in direct sunlight may affect aesthetics if the Savannah dries too quickly. Avoid direct sunlight.
- Use of Clearshield sealer is recommended in high moisture or traffic areas.
- When cleaning do not use harsh or abrasive cleaners. Wash gently using a soap and water solution followed by a warm water rinse.

Clean Up

Tools and equipment can be cleaned with soapy water while the Savannah is still wet. Product description information and basic uses etc.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2020 Master Wall Inc.®



masterwall.com

PO Box 397 • Fortson • GA • 31808 • 800-755-0825