



## PLASTIC ACCESSORIES

Available from a variety of manufacturers, plastic accessories are used as part of Master Wall Continuous Insulation and Finish Systems (CIFS®), Exterior Insulation and Finish Systems (EIFS) and Stucco Cement Board Coatings. Accessories for drainage systems would be ordered with drainage holes to allow for drainage.

### FEATURES & BENEFITS

- Eliminates the need for backwrapping
- Can be used as a drainage flashing when incorporated into a drainage system.
- Reveals available for Stucco Cement Board Coating systems as well as other direct applied systems
- UV Resistant
- Good bonding surface for sealants

Application Temperature: 40°-110°F (5°-43°C) Working Time: 1/4 hr. Set Time: 8-12 hrs. Dry Time: 48-72 hrs. at room temperature, working and drying time will vary with temperature and humidity.

### APPLICATION PROCEDURE

Accessories shall be erected true to line (allowable tolerance of 1/4" in 10' (6.4 mm in 3.05 m), level, plumb, squared or curved.

Casing beads at grade (drainage or non-drainage) shall be placed not less than 1" (25 mm) below the joint formed by the foundation and framing and placed not less than 6" (152 mm) above raw earth. 2" (51 mm) above paved surfaces or 3/4" (19 mm) above supported slabs not subject to frost heave.

Drainage systems shall have the weather-resistive barrier lapped into the casing bead.

Attach accessories to the substrate in such a manner as to ensure proper alignment during the application of the accessories shall be secured at not more than 16" (406 mm) centers for non-nailable substrates and 8" (203 mm) on center for nailable.

Seal all butt joints, intersections, ends and corners at time of installation using an elastomeric sealant. Allow silicone-based sealant to fully cure before proceeding with insulation board application.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2024 Master Wall Inc.®



### Systems

- Aggre-flex EIFS
- Aggre-flex Drainage EIFS
- QRW1 Drainage EIFS
- Rollershield Drainage CIFS®
- Stucco Cement Board Coatings
- Soffit System
- UF Systems

Packaging:: Typically 10' lengths

Weight: Varies

Typical Widths: 3/4" to 4" (19-102 mm)

### Manufacturers

Amico Building Products 800-366-2642  
[www.amico-lath.com](http://www.amico-lath.com)

Plastic Components 800-327-7077  
[www.plasticcomponents.com](http://www.plasticcomponents.com)

Vinyl Corp. 800-648-4695  
[www.vinylcorp.com](http://www.vinylcorp.com)

Wind-Lock 800-872-5625  
[www.wind-lock.com](http://www.wind-lock.com)

Product Test Standards  
ASTM D1784, ASTM C1063, ASTM D4216, May not be suitable for noncombustible construction assemblies.