



PRODUCT DATA

BRICK FINISH

Create faux brick finishes using Master Wall Superior Finishes. The choice is yours with this highly customized brick finish and you can vary the finish textures, mortar colors and accent techniques using Vintique.

FEATURES & BENEFITS

- Interior or Exterior
- Create brick or stone looks
- Applies over EIFS, Stucco or other approved substrates
- Light weight, no extra footings needed
- Your choice of mortar and brick colors

Brick look finishes are becoming a popular method of finishing off EIFS or stucco projects. They can offer an effective representation of brick or stone without the weight or difficulty of installation. Of course, much is dependent upon the skill and creativity of the applicator.

APPLICATION TECHNIQUE AND OPTIONS

The steps involved are relatively simple. If the installation is over EIFS® OR EIFS, the wall must be meshed and base coated, ready for finish. Stucco and One Coat Stuccos must be cured, dry and ready for a finish coat. Typical applications include the following steps:

- “Mortar” Color Application, typically Versatex Texture or Superior-Cote™ over a smooth base coat
- Stencil Application. The poly coated stencils are self adhesive
- “Brick” Color Application, usually Versatex
- Texturing to meet desired texture
- Optional accenting as needed with Vintique

Creating these looks is more art than science. You may find the need to vary the techniques to suit your particular project.

Coverage per pail (sf/m²)*

Versatex 0.5 over stencil in a smooth texture, 160-170 (15-15.8)

SuperiorCote™ option for faux mortar joints

- 1-gallon: 250-400 sf (23-37) @ 4 mils wet; 1.5 mils dry
- 5-gallon: 1250-2000 sf (115-185) @ 4 mils wet; 1.5 mils dry

**All coverage is approximate and depend upon substrate, details and individual application*

Stencil Recommendation

Universal Templates Poly Coated Cardboard, standard and custom patterns available

Universal Templates
PO Box 2137
Fortson, GA 31808
Phone: (603) 321-1286
Office: (888) 568-4128
orders@universaltemplates.com
universaltemplates.com

TYPICAL APPLICATION



Select "Mortar" and "Brick" Color. "Mortar" could be SuperiorCote™



Apply Mortar Color



Place Stencil over dried "Mortar"



Apply and Texture "Brick" Color



Remove Stencil as brick color is setting up



Once dry Accent with Vintique (optional) if desired

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2024 Master Wall Inc.®

