



PRODUCT DATA

QUICK DRY

Drying Accelerator for Master Wall® Superior & Superior Elastomeric Plus Finishes

FEATURES & BENEFITS

- Accelerates drying time by as much as 25%
- Allows projects to be completed faster
- Improves finish hardness and mar/scuff resistance
- Promotes strong adhesive bond to wall surface
- Inhibits growth of mildew
- For use in cool, moist climates

APPLICATION PROCEDURE

1. Follow the mixing instructions for Master Wall Inc. Superior and Superior Elastomeric Plus Finishes. Thoroughly mix in all tints prior to adding Quick Dry.
2. Pour the vial of Quick Dry into the mixed finish and remix. For color consistency add Quick Dry to all pails as needed to go from corner-to-corner.
3. Dry times will vary depending on weather temperature and relative humidity.

LIMITATIONS: Ambient and surface temperature must be 40°F (4.4°C) or higher during application and curing time. Provide supplemental heat and protection from precipitation as needed. An Acrylic or Elastomeric Finish that the Quick Dry has been added to should be tightly sealed during storage to avoid setting up in the pail.

This product contains ammonia, mix in a well ventilated area and wear an approved respirator, protective glasses, and gloves. Reference the SDS sheet for specific safety instructions.

CLEAN-UP: Water-soluble prior to drying. Clean tools and containers with water before mixture sets.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2024 Master Wall Inc.®

Packaging/Shelf Life/Storage

Packaging: 4 oz (118 ml) vial
24 vials/case
Shelf Life: 2 years

Storage: Protect from extreme heat - 90°F (32°C), freezing and direct sunlight.

Hazard: This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

