



**Master Wall Inc.**  
Building a Culture of Excellence

## PRODUCT DATA

### CIFS® WOOD GRAIN GLAZE

#### CIFS® WOOD GRAIN SPECIALTY FINISH

CIFS® Wood Grain Glaze used artistically over Wood Grain Tex specialty finish creating the look of wood with the durability of an acrylic finish and is formulated with DuroTone pigments for excellent color retention.

#### FEATURES & BENEFITS

- Glazing and accent coating for the CIFS® Wood Grain application procedure
- Integrally colored
- Standard and custom colors available

Application Temperature: 40°-110°F (5°-43°C)

Working Time: 1/2 hour

Dry Time: 12 hours at room temperature, working and drying time will vary with temperature and humidity.

#### JOB CONDITIONS

Air and substrate temperature for application must be 40°F (5°C) or higher and must remain 40°F (5°C) or higher for a minimum of 24 hours. Provide temporary protection to protect the wall system from damage until permanent flashings, caps and sealants are installed. Store materials within prescribed temperature limits and out of direct sunlight. High temperatures will reduce working times, Low temperatures and/or high humidity and pigment loading will extend working, set and dry times.

Store materials within prescribed temperature limits and out of direct sunlight. Working and drying times are based upon normal room temperature conditions and will vary with temperature and humidity.

#### PREPARATION

The Wood Grain Tex Finish must be clean, dry, and ready to receive the acrylic coating.

Equipment Needed - Brush, 4"-6" (102-154 mm) Foam Roller, Spray bottle with water, Wood Grain Tool (Available from Master Wall®), Wood Grain Sealer.

Mixing - Thoroughly stir Wood Grain Glaze into a homogenous consistency. Small amounts of clean, potable water may be added to obtain a workable consistency. Do not over mix. Do not exceed 24 ounces (0.7 L) of water per pail. Do not add accelerators or retarders to Wood Grain Glaze.

#### Coverage per pail (sf/sm)\*

1000-1200 sf/pail (93-112 sm)

*\*All coverage is approximate and depend upon substrate, details and individual application*

#### Packaging/Shelf Life/Storage

Packaging: 5 gallon (19L) pail

Shelf Life: 2 years

Storage: Protect from extreme heat - 90°F (32°C), freezing and direct sunlight.

**Hazard:** This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

**VOC:** Less than 50 g/L.

See Superior Finishes for other technical properties

#### Approved Substrates

CIFS® Wood Grain Tex

Others approved in writing

## APPLICATION PROCEDURE

Wood Grain Glaze is applied by brush or a moist foam roller. Using a paint brush for latex paints, brush Wood Grain Glaze into the grooves of the finish. Using a moist foam roller, roll a thin amount of Wood Grain Glaze onto the finish surface and keep a wet edge. Using a spray bottle, wet the surface of the Wood Grain Glaze to thin and keep from tacking too quickly.

Add grain to the surface using the Wood Grain Tool along the length of the grooved finish, rocking the tool to create the desired pattern. Once dry to the touch, lightly sand the surface if needed using 100-grit sandpaper to remove any high spots or heavy stain areas.

Using a sponge or foam roller, cover the entire surface with CIFS® Wood Grain Sealer.

## CAUTIONS AND LIMITATIONS

Do not use Wood Grain Glaze as a finish directly over any Master Wall base coat.

## CLEAN UP

Tools and equipment can be cleaned with soapy water when Wood Grain Glaze is wet.

Information contained in this product data sheet conforms to the standard detail recommendations and specifications for the installation of Master Wall Inc.® products and is presented in good faith. Master Wall Inc.® assumes no liability, expressed or implied as to the architecture, engineering, or workmanship of any project. This information may be concurrent with, or superseded by other applicable documents, such as specifications and details. Contact Master Wall Inc.® for the most current product information. ©2023 Master Wall Inc.®

## Health & Safety

### WARNING!

Causes eye and skin irritation.

Precautionary Statement

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

### FIRST AID MEASURES

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get immediate medical attention.

**Skin Contact:** Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Store locked up. Dispose of contents/container in accordance with Local, State, Federal and Provincial regulation.

**Spills:** Collect with suitable absorbent material such as cotton rags.

**Disposal:** Dispose of in accordance with local, state or federal regulations.

Warning: KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP OUT OF THE REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.

Consult the Safety Data Sheet (SDS) in the Products section at [masterwall.com](http://masterwall.com) for further health and safety information.

### LIMITED WARRANTY

This product is subject to a written limited material or system warranty. Obtain a warranty from the Tech Support tab of our website. Refer to Specifications for more complete information on proper use and handling of this product.